



SPECIFICATION SHEET

Floor Grip

Product: 222 Series **Acrylic Modified Alkyd Aggregate Coating**

10/2019

DESCRIPTION:

Floor Grip is a non-slip, non-skid alkyd aggregate coating for steel, aluminum and masonry surfaces. It contains a special aggregate combination which withstands rough weather conditions and daily wear and tear.

RECOMMENDED USES:

Floor Grip is for use on steel, aluminum or concrete masonry surfaces such as; decks, porches, walkways, ramps, steps, boat decks, bridgeways and numerous other industrial applications. **NOT FOR USE ON WOOD SURFACES.** For wood surfaces use **Farwest Deck Safe** (2001 Series).

SURFACE PREPARATION:

Clean all surfaces of oil, dirt, grease, corrosion and any existing paint that lacks good adhesion. Temperature must be a minimum of 50°F to apply **Floor Grip**. Steel, aluminum and masonry should be etched with Farwest 695 Rynolite Chemical Cleaner-Etcher. For optimum adhesion a primer should also be applied. Prime aluminum surfaces using a fog coat of **Zinc Chromate Wash Primer**. Prime steel surfaces using **Farwest Lacquer Proof Primer**.

COVERAGE: 75 sq. ft. per gallon.

THINNING: Thinning is not recommended. If absolutely necessary use 605 Synthetic Thinner.

APPLICATION: Stir thoroughly. Apply by brush or roller.

CLEAN-UP: Equipment and tools may be cleaned with 605 Synthetic Thinner or 610 Lacquer Thinner.

DRY TIME:

Dry to touch in 1 hour. Tack free in 2 hours. Recoat in 8 hours. Dries hard in 8 hours.

COLORS & TINTING: Unlimited Range of Colors

CAUTIONS:

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

CAUTIONS CONTINUED:

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

KEEP OUT OF REACH OF CHILDREN.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DISPOSAL OF OILY RAGS: Rags and other waste materials soiled with this product may spontaneously catch fire if improperly discarded. Soak soiled rags and waste immediately after use in a water-filled, closed metal container.

VEHICLE TYPE: Alkyd Fortified, Natural Oils

WEIGHT PER GALLON: 14 pounds per gallon.

% SOLIDS: 59-62% by volume. 79-81% by weight.

FLASH: 80°F

V.O.C.: Maximum 350 grams per liter.

VISCOSITY: 125 k.u.

In Case of Chemical Emergency call ChemTrec (24hr): 1-800-424-9300

Farwest Paint Mfg Co

4522 S 133rd St ~ Tukwila, WA ~ 98168

www.farwestpaint.com

T: (206) 244-8844 F: (206) 246-7691