



SPECIFICATION SHEET

Wonderglo® Quick Dry Enamel

Product: 250 Series

Pigmented Gloss Alkyd Enamel

10/2019

DESCRIPTION:

Wonderglo is a durable enamel suitable for use on cabinets, furniture, tools, toys, machinery etc. It is used widely as an excellent marine and equipment enamel finish which withstands all types of weather conditions. The fully cured finish can withstand repeated washing and normal everyday abuse. It has proven its performance in an industrial and commercial maintenance fields, where frequent washing is necessary and when used as a gloss interior or exterior trim enamel.

RECOMMENDED USES:

Wonderglo is for use on cabinets, furniture, tools, toys, machinery, etc.

SURFACE PREPARATION:

Surface must be clean, dry, properly prepared and free of dirt, grease or loose chipping paint and particles. Glossy surfaces must be de-glossed with **644 Gloss-Set** or sandpaper before finishing. New or bare wood surfaces should be primed with **710 Oil Primer**. New or bare metal surfaces should be primed with **X-4576 Red Oxide Primer** before applying finish coat.

COVERAGE: 300-500 sq. ft. per gallon depending on application.

THINNING: Thin if necessary with 602 Mineral Spirits or 605 Synthetic Thinner.

APPLICATION: Brush, roller, airless or conventional sprayer. This material needs little or no thinning for brushing and rolling.

CLEAN-UP: Equipment and tools may be cleaned with 605 Synthetic Thinner or 602 Mineral Spirits.

DRY TIME:

Dry to touch in 1 hour. Tack free in 6-8 hours. Time to recoat is overnight. Dries hard in 8 hours.

COLORS & TINTING:

Standard Colors: 250 White, 251 Deep Base, 252 Clear Base, 253 Mandarin Red, 255 Forest Green, 257 Delphinium Blue, 259 Black, 260 Canary Yellow, 261 Orange. Can also be tinted to other colors.

VEHICLE TYPE: Alkyd Enamel

WEIGHT PER GALLON: 7.6-9.5 pounds per gallon.

% SOLIDS: 42-45% by volume. 50-60% by weight.

FLASH: 107°F

V.O.C.: Maximum 439 grams per liter.

VISCOSITY: 70-80k.u.

CAUTIONS:

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

Precautions: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Ground and bond container and receiving equipment. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. DISPOSAL OF OILY RAGS: Rags and other waste materials soiled with this product may spontaneously catch fire if improperly discarded. Soak soiled rags and waste immediately after use in a water-filled, closed metal container.

In Case of Chemical Emergency call ChemTrec (24hr): 1-800-424-9300

Farwest Paint Mfg Co

4522 S 133rd St ~ Tukwila, WA ~ 98168

www.farwestpaint.com

T: (206) 244-8844 F: (206) 246-7691