FARWEST PAINT PRODUCT INFORMATION Primers & Pre-Treatment Coatings

X-4959

X-4959 Weatherguard Red Lacquer Proof Primer

Revised 4/18/97

COLOR(S): Red Oxide.

PRODUCT TYPE: Phenolic Modified Alkyd Primer.

DESCRIPTION: A high grade phenolic modified alkyd type rust-inhibiting primer for application on iron, steel,

or wood. This product offers an excellent combination of properties including fast-drying, good adhesion over properly prepared surfaces and good protection against rusting. It is a lacquer proof primer which means that finish coats such as nitrocellulose lacquers may be applied directly over it without lifting or wrinkling. It is the recommended primer for use with

Farwest Skythane Two-Component Urethanes.

Intended Use: For iron, steel, or wood surfaces.

PHYSICAL CHARACTERISTICS

VISCOSITY: 55-60 k.u. DRY TO TOUCH: 30 minutes

WEIGHT SOLIDS: 48-50% TACK FREE: 1 hour

VOLUME SOLIDS: 33-35% TIME TO RECOAT: 1 hour

WEIGHT PER GALLON: 9.40 lbs. per gal. DRY HARD: 2 hours

V.O.C.: 563 grams per liter COLOR RANGE: Red Oxide

FLASH POINT: 50° F. PACKAGING: 1 or 5 gallon containers

PRACTICAL BATCH: Stock

COVERAGE: 300 square feet per gallon @ 2 mils dry film thickness.

SURFACE

PREPARATION: Remove loose rust and scale with Farwest #695 Rynolite Chemical Cleaner-Etcher and wire

brush. All surfaces should be free of foreign particles and contaminants.

APPLICATION: Spray application is recommended for best results. For conventional spray: thin to 20-24" Zahn

#2 Cup.

THINNING: This product should not be thinned unless absolutely necessary. If necessary for even spraying,

thin with Farwest #605 Synthetic Thinner.

CLEAN-UP: Tools and equipment may be cleaned with Farwest #605 Synthetic Thinner or Farwest #615

Wash Thinner.

FARWEST PAINTS □ Monderglo® Paints • jarvie™ paints • MATSON™ PAINTS

"Built For Performance-Made With Pride"

FARWEST PAINT MANUFACTURING CO. 4522 South 133rd, P. O. Box 68726

Tukwila, Washington 98168
(206) 244-8844 • FAX: (206) 246-7691
1-800-727-9694

"Quality Paints Since 1925"

LIMITED WARRANTY. To the best of our knowledge, the technical data presented above is true and accurate at the date of issuance and subject to change without prior notice. Farwest Paint Manufacturing Co. guarantees its products to conform to its standards of quality control. Liability is limited to replacement of product. No other warranty or guarantee of any kind is made by Farwest Paint Manufacturing, implied or otherwise.